




HIGGS™ 9

HIGH CAPACITY GS1 CLASS 1 GEN 2 RFID TAG IC

Featuring industry leading **data integrity & reliability**, **Higgs 9™** delivers cutting edge **read / write sensitivity** and **flexible memory capacity** designed to fit with today's demanding applications and the evolving IoT information base.



FEATURING



APPLICATIONS

- **Aviation**
- **Automotive**
- **Dynamic memory structure**
- **High sensitivity**

Feature	Description	Benefit
Sentinel™ Memory	Detects and fixes single bit errors and flags dual bit errors.	Safeguarded data and immunity to typical sources of single bit errors (chip damage, low power etc.)
Read sensitivity	Up to -20 dBm*	Allows smaller tags to be designed or larger read & write distances to be realized.
Write sensitivity	Up to -18 dBm*	
Best in class memory reliability	200,000 write cycles	Robust memory retention (twice that of competition)
96 bit expandable EPC	Supports EPC size up to 496b for flexibility.	Additional 400 bits allows storing of larger identifying information.
688 bit user memory	User memory for storage of additional application data.	For applications requiring data beyond EPC (asset data, service history, usage info etc.)
48b UTID with lower 38b unique serial for SGTIN generation	48b UTID. Lower 38b are duplicated in the EPC for SGTIN generation.	For retail and general serialization
Larger “pads” for improved antenna connectivity	More contact area for antenna connectivity	Increased and more consistent yield inlay to inlay

*on a 2.15 dBi gain dipole antenna

Features:

- › Compliant to GS1 Class 1 Gen 2 and ISO/IEC 18000-6C
- › Worldwide operation in the RFID UHF bands (840-960 MHz)
- › 1024-Bits of NVM/RAM Memory
 - Up to 496-EPC Bits (nominally 96 bits)
 - Up to 688 User Bits
 - **48 Bit Unique TID**
 - 32 Bit Access and 32 bit Kill Passwords
- › Pre-Programmed with a unique, unalterable 48-bit serial number
- › User Memory can be Block Perma-Locked as well as read password protected in 256 bit Blocks
- › Low power operation for both read and program
- › QuickWrite™ / BlastWrite™- High-speed chip & mass programming
- › Dynamic Authentication™ anti-cloning / anti-counterfeit technology
- › Exceptional operating range, up to 13m with appropriate antenna.

Product Overview:

Featuring pioneering Sentinel Memory™ bit error correction, world class sensitivity, expandable EPC memory and expansive User Memory, **Higgs 9** offers cutting edge performance and data storage capability suitable for today's ever evolving and demanding application base.

Ideal for the high memory requirements of Aviation part tagging / tracking and any application requiring data storage at tag and asset level. In addition, applications requiring asset data and/or longer serialization in the EPC memory area may utilize Higgs 9's configurable EPC memory. Up to 496 bits (124 Hexadecimal characters) may be written to the EPC memory area. This allows increased flexibility to store data such as extended serial numbers, product SKU #, service hours, dates, history etc.

Like all Alien ICs, Higgs 9 is fully backward compatible with the entire Alien IC and Reader portfolio feature-set. Alien's mass-encoding capabilities (**QuickWrite™** and **Blast-Write™**) and Aliens anti-cloning technology (Dynamic Authentication™) are supported.



HIGGS 9 WITH SENTINEL MEMORY

HIGH CAPACITY EPCGLOBAL CLASS 1 GEN 2 RFID TAG IC

Operating Conditions & Electrical Characteristics

Symbol	Parameter	Conditions / Capability	Min	Typ	Max	Units
Operating Conditions						
T _A	Operating Temperature		-50	+25	+85	°C
f _{in}	Operating Frequency		840		960	MHz
Electrical Characteristics						
S _R	Sensitivity during Read	Bare die measurement, matched to 50 Ohm source impedance, Calibrated Voyantic™ measurement system		-17.7		dBm
S _W	Sensitivity during Write			-15.8		dBm
I _S	Interference Signal Suppression			-4		dB
R _P	Equivalent input parallel resistance			2,500		Ohms
C _P	Equivalent input parallel Capacitance			0.85		pF
D _{ret}	Data Retention			50		Years
P _{cycl}	Programming Cycles at 25°C			200,000		Cycles

Physical Die Characteristics

Dimension	Description	Size	Units
x	Horizontal die length	566	µm
y	Vertical die height	453	µm
z	Die thickness	150 +/- 10	µm

Memory Map

Bank	Address	Description	Memory	Bits
User	000h – 2AFh	User	NVM	688
TID	60h & above	Device Configuration	ROM-NVM-SRAM	-
	30h – 5Fh	Unique Tag ID Unalterable	NVM	48
EPC	00h – 2Fh	XTID*/TID EPC/TMD/TMDID/TMN	ROM	48*
	20h – 7Fh	EPC #	NVM	96
	10h – 1Fh	EPC-PC	NVM	16
Reserved	00h – 0Fh	EPC-CRC	RAM	16
	20h – 3Fh	RES-Access Pwd, EPC optional	NVM	32
	00h – 1Fh	RES-Kill Pwd	NVM	32


*Higgs 9 follows the XTID/TID format which manifests in an additional word between the manufacturer code and the UTID words versus Higgs-3 and Higgs-4. To read the same UTID word in Higgs 9 as in Higgs-4, shift the read location by one word. All other memory banks are identical to Higgs-4 (e.g. Reserved, EPC and User memory are the same as Higgs-4).

Ordering Information

Part	Model Number	Description
Higgs 9™ IC	ALC-390-IC	Bumped, Tested, Ground & Sawed IC's. Provided on 8 Inch Wafer, UV Tape Mounted (SEMI/JIS Standard Metal Film Frame)
	ALC-390-SOT	SMD Package: SOT-323



Wafer and Die Size and Orientation






HIGGS 9 WITH SENTINEL MEMORY

ALIEN. HIGH CAPACITY EPC GLOBAL CLASS 1 GEN 2 RFID TAG IC

Pad Placement and Dimensions

All dimensions are in thousandths of a millimeter and +/- 10%



February 21, 2020

Copyright © 2020 Alien Technology LLC. All rights reserved.

Alien, Alien Technology, the Alien Technology logo, Spider, Higgs, Dynamic Authentication, QuickWrite, BlockWrite, Squiggle, and the Squiggle logo are trademarks or registered trademarks of Alien Technology Corporation in the U.S. and other countries.

HANDLING PRECAUTIONS Observe standard handling practices to minimize ESD.

DISCLAIMER Application recommendations are guidelines only - actual results may vary and should be confirmed. This is a general purpose product not designed or intended for any specific application.

This product is covered by one or more of the following U.S. patents: 7967204, 7931063, 7868766, 7737825, 7716208, 7716160, 7688206, 7671720, 7659822, 7619531, 7615479, 7598867, 7580378, 7576656, 7562083, 7561221, 7559486, 7559131, 7554451, 7551141, 7542301, 7542008, 7522055, 7500610, 7489248, 7453705, 7452748, 7425467, 7417306, 7411503, 7385284, 7377445, 7364084, 7353598, 7342490, 7324061, 7321159, 7301458, 7295114, 7288432, 7265675, 7262686, 7193504, 7173528, 7172910, 7172789, 7141176, 7113250, 7101502, 7080444, 7070851, 7068224, 7046328, 6998644, 6988667, 6985361, 6980184, 6970219, 6952157, 6942155, 6933848. Other patents pending.

This product is licensed under patents of Round Rock Research, LLC, for use solely with UHF RFID Readers (such as Alien reader products) that are licensed under an agreement with Round Rock Research, LLC.



Alien Technology
845 Embedded Way.
San Jose, CA 95138
www.alientechnology.com